IF2012B



Version 11.0

IRIS 2002,S.A.
C/San Agustin, 17 28014 Madrid SPAIN
T. +34 91 429 42 99 F.+34 91 369 05 93
www.irisled.com

Features and Benefits



- Waterproof:

Adopt new patent of air filter device for preventing moisture condensation inside the luminaire.

- Mounting:

Vertical & horizontal angle adjustment.

- Quality components:

1.Integrated heating solution to guarantee the LED luminous efficiency and life span.

2.Imported silicon rubber material is adopted for waterproof gask

3.Universal voltage converter: AC100-240V+10%

Code & Reference

20111103	**IF2012B-18X3W-40deg-RE-RGB-(AC100-240V)**
20111104	**IF2012B-18X3W-40deg-RE-R-(AC100-240V)**
20111105	**IF2012B-18X3W-40deg-RE-G-(AC100-240V)**
20111106	**IF2012B-18X3W-40deg-RE-B-(AC100-240V)**
20111107	**IF2012B-18X3W-40deg-RE-A-(AC100-240V)**
20111108	**IF2012B-18X3W-40deg-RE-WDL-(AC100-240V)**
20111109	**IF2012B-18X3W-40deg-RE-WA-(AC100-240V)**

Available beam angles:


Single color: 15°，25°，40°，60°


RGB： 15°，25°，40°，60°， 4525


Technical Parameter


Product type	IF2012B
LED	LUMILEDS
Single LED Wattage	3W
LED life span and warranty	50,000 hours, 2 years warranty
LED Quantity	18 pcs
LED color (single color)	Red Amber Green Blue White Warm White
LED color (color changing)	Multiple colors can be created
Beam angle	See lens options
Housing	Die-cast aluminium, powder paint with high corrosion resistance
Glass material	8mm thickness tempered glass, Aluminum gray finish
Power input	AC100-240V±10%; 50/60Hz
LED driver	700mA constant driver
Power consumption	67W (single color), 71W (color changing)
Anti-static	IEC61000-4 (Level 4)
Ingress protection	IP66
Classification	I
Power supply cable	3x1.00mm^2 rubber cable
Signal cable	Double screen for 4 pairs signal cable STP-5E
Control	DMX512 Compatible (1990)
Ambient operating Temperature	-20ºC to +55ºC (Ta +10ºC)
Net weight	5.1 Kg

Dimensions (mm)










IRIS 2002,S.A.
C/San Agustin, 17 28014 Madrid SPAIN
T. +34 91 429 42 99 F.+34 91 369 05 93
www.irisled.com

Distribution Curve




Color	Total output	Power (W)
White	2202 lm	67

System Control (single color)



Remarks: (1) Maximum serial connective number of lights is 10PCS, new power cable is needed for over 10PCS;
(2) Maximum serial connective number of lights is 4PCS for input voltage DC36V

System Control (color changing)



Remarks: (1) Maximun serial connective number of lights is 10PCS, new power cable is needed for over 10 PCS;
(2) Maximun serial connective number of lights is 4PCS for input voltage DC36V
(3) Lenght of signal cable is more than 300m or number of lights is more than 32PCS, new booster is needed.

Remarks: (1) For the information of power cable-first cable, power cable-last cable, signal cable-first cable, signal cable-last cable, please refer to the accesories.

IRIS 2002,S.A.
C/San Agustin, 17 28014 Madrid SPAIN
T. +34 91 429 42 99 F.+34 91 369 05 93
www.irisled.com