SLIM LED PANEL-II





IRIS 2002, S.A.
C/ San Agustín, 17 28014 Madrid SPAIN
T. +34 91 429 42 99 F. +34 91 369 05 93
www.irisled.com

Version 11.0

Features and Benefits

- 50% energy savings and virtually free-maintenance


Input Voltage	AC85-265V
Power Consumption	60W
Lumen Output	WDL: 5216lm WW: 4575lm
System efficacy	80lm/W
Color Temperature	3000K, 4500K, 6500K
CRI	70
Operation Temperature	-20ºC to +45ºC
Certificates	CE


Lifetime & Warranty

Expected lifetime: 40.000 hrs

Warranty: 2 years

Dimensions





Code & Reference

20370043	**LED slim panel- 600x600mm 3000K**
20370044	**LED slim panel- 600x600mm 4500K**
20370183	**LED slim panel- 600x600mm 6500K**

Application

Commercial & Office Lighting

Warehouse & Supermarket Lighting


Retail: Shops and Showrooms

Restaurants, Hospitals, Hotels


Other public places

IRIS 2002, S.A.
C/ San Agustín, 17 28014 Madrid SPAIN
T. +34 91 429 42 99 F. +34 91 369 05 93
www.irisled.com

Distribution Curve




Average beam angle (50%) : 114.0 degree



Average beam angle (50%) : 113.5 degree

Installation



IRIS 2002, S.A.
C/ San Agustín, 17 28014 Madrid SPAIN
T. +34 91 429 42 99 F. +34 91 369 05 93
www.irisled.com