




IF3034B



IRIS 2002, S.A.
C/San Agustin, 17 28014 Madrid SPAIN
T. +34 91 429 42 99 F.+34 91 369 05 93
www.irisled.com

Features and Benefits

● Waterproof:

Adopt new patent of air filter device for preventing moisture condensation inside the luminaire.

● Mounting:

Vertical & horizontal angle adjustment.

● Quality components:

- 1.Integrated heating solution to guarantee the LED luminous efficiency and life span.
- 2.Imported silicon rubber material is adopted for waterproof gask
- 3.Universal voltage converter: AC100-240V+10%

Technical Parameter


Product type	IF3034B
LED	LUMILEDS
Single LED Wattage	3W
LED life span and warranty	50,000 hours, 2 years warranty
LED Quantity	36pcs (Single color) ; 48pcs (color changing)
LED color (single color)	Red Amber Green Blue White Neutral white, Warm White
LED color (color changing)	Red,Green, Blue
Beam angle	15°, 25°, 40°, 60°, 4525(RGB)
Housing	6063 aluminium,anode dioxide finish
Glass material	5mm thickness tempered glass, Aluminum gray finish
Power input	AC100-240V±10%; 50/60Hz
LED driver	700mA constant driver
Power consumption	135W (Single color) ; 160W (color changing)
Anti-static	IEC61000-4 (Level 4)
Ingress protection	IP66
Classification	I
Power supply cable	3x1.00mm ² rubber cable
Signal cable	Double screen for 4 pairs signal cable STP-5E
Control	DMX512 Compatible (1990)
Ambient operating Temperature	-20°C to +55°C (Ta +10°C)
Net weight	5.2 Kg

Code & Reference


20112686	IF3034B-36X3W-25deg-RE-R-(AC100-240V)
20112687	IF3034B-36X3W-25deg-RE-G-(AC100-240V)
20112688	IF3034B-36X3W-25deg-RE-B-(AC100-240V)
20112689	IF3034B-36X3W-25deg-RE-A-(AC100-240V)
20112690	IF3034B-36X3W-25deg-RE-NW-(AC100-240V)
20112691	IF3034B-36X3W-25deg-RE-WDL-(AC100-240V)
20112692	IF3034B-36X3W-25deg-RE-WA-(AC100-240V)
20112693	IF3034B-48X3W-25deg-RE-RGB-(AC100-240V)

Single color: 15°, 25°, 40°, 60°
 RGB: 15°, 25°, 40°, 60°, 4525

Dimensions (mm)



Distribution Curve



Color	Total output	Power (W)
White	4168lm	96

System Control (single color)



- Remarks:
- (1) Maximum serial connective number of lights is 8PCS, new power cable is needed for over 8PCS;
 - (2) Maximum serial connective number of lights is 2PCS for input voltage DC36V

System Control (color changing)



- Remarks:
- (1) Maximum serial connective number of lights is 8PCS, new power cable is needed for over 8 PCS;
 - (2) Maximum serial connective number of lights is 2PCS for input voltage DC36V
 - (3) Length of signal cable is more than 300m or number of lights is more than 32PCS, new booster is needed.