


FLEXSTRIP BASIC RGB



Features and Benefits




- RGB
- SMD5050 as light source
- High Luminance
- Self Cooling: No heat sink surface needed
- Can be installed over any material or surfaces
- Long lifetime and energy saving
- No damaging heat (IR) or UV
- Virtually-free maintenance
- Robust for easy transportation and installation
- Low Voltage 12V DC
- Wide Operating Temperature: -40°C to +45°C

Product Shot



IP45



IP68

Lifetime & Warranty

Expected life time: 30.000hrs
 Warranty: 2 years


Packaging



1 Roll = 5m



1 Pack = 1 Roll




1 Box = 60 Roll = 300m

Technical Performance

Code	Reference	LED Qty	Voltage	IP	Power / Meter (W/M)	Color	Luminous Flux (lm/mtr)	Cutting Unit	Continous Connection	Size(mm)
20250496	FLEXSTRIP BASIC RGB 5m/roll IP65	300/Roll	DC12V	68	14.4	RGB	360	3 LEDs	5m	5000x12x4
20250497	FLEXSTRIP BASIC RGB 5m/roll	300/Roll	DC12V	45	14.4	RGB	324	3 LEDs	5m	5000x12x4

Connection

- Connect to the appropriate power supply (DC12V)
- Each 5 meters need a DC12V 100W driver



Cut to desired length, over the cutting mark printed on the product



Expose the adhesive side by removing the cover layer of the double sided tape affixed to the product.



Adhere the product to the desired place



Angle connection



In-line connection



Solder leads to switching power supply

Applications

1. Architectural decorative lighting and backlighting for homes, hotels, marketplaces, bars etc.
2. Auditorium walkway lighting, illuminated signs and advertisements
3. Illumination lighting used for walkway, canopy, stairway accent and amusement park
4. Car interior and exterior lights
5. Channel letter lighting used for stores, restaurants, bars

